

# J200 SA

## Retractable bollard



Type of operator

Semiautomatic

Height

600 mm

- Power supply and wiring not requested
- Kept lock in low position (against accidental release).
- Simple and safe movements thanks to the dedicated release key
- Simplified placement thanks to the self-supporting structure which does not require a pit.



### DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	J200 SA H600	J200 SA H600 Stainless steel
Type of operator		Single-acting gas operator
Cylinder height from ground		600 mm
Cylinder diameter		200 mm
Cylinder material	S235JRG2 EN 10277 steel	AISI 316L satin finish
Cylinder treatment	Cataphoresis and polyester powder paint, dark grey metallised RAL 7021	Satin finish
Release device		Key operated (supplied)
Reflective strip height		25 mm
Standard reflecting strip colour		Orange
Total weight		82 Kg
Walled in pit with cylinder profile (LxWxH)		400 x 500 x 800 mm
Excavation dimensions (LxWxH)		700 x 700 x 1.100 mm
Load class (EN 124)		C250

## PAINTED STEEL FAMILY MODELS

Model	Item code
J200 SA H600	116508

## PACKS

### J200 SA is equipped with:

- steel cylinder with cataphoresis treatment and metallised dark grey powder coated painting
- support structure to be cemented with cataphoresis treatment (pit not required)
- Release key (1 pc)

## INOX AISI 316L FAMILY MODELS

Model	Item code
J200 SA H600 Stainless steel	116509

## PACKS

### J200 SA INOX is equipped with:

- AISI 316L satin-finished stainless steel cylinder
- support structure to be cemented with cataphoresis treatment (pit not required)
- Release key (1 pc)

## OPTIONAL ACCESSORIES



LED lights kit J200 ♦

116504



Release keys kit (5 keys)

390084

## NOTE

- ♦ The power supply unit (24 V) and the cable (2x1.5 mm) for the flashing light are not supplied.