

# J275 F 2K20

## Fixed traffic bollard



Type of operator

Fixed

Height

800 mm

- Power supply and wiring not required
- “Shallow Mounted” design: minimum hole depth required
- Visually identical to the retractable (HA) models, making it perfect for mixed installations



### DIMENSIONS AND TECHNICAL SPECIFICATIONS

| Model                            | J275 F 2K20 H800                    | J275 F 2K20 H800 INOX |
|----------------------------------|-------------------------------------|-----------------------|
| Cylinder height from ground      |                                     | 800 mm                |
| Cylinder diameter                |                                     | 275 mm                |
| Cylinder treatment               | Cataphoresis and polyester painting | Satin finish          |
| Reflective strip height          |                                     | 55 mm                 |
| Standard reflecting strip colour |                                     | Yellow                |
| Break in resistance              |                                     | 656.000 J             |
| Total weight                     |                                     | 110 Kg                |

## PAINTED STEEL FAMILY MODELS

| Model            | Item code |
|------------------|-----------|
| J275 F 2K20 H800 | 116421    |

## PACKS

The J275 F 2K20 comes with:

- steel cylinder with cataphoresis treatment and metallised dark grey powder coated painting
- flashing LED lights ring\*

## INOX AISI 316L FAMILY MODELS

| Model                 | Item code |
|-----------------------|-----------|
| J275 F 2K20 H800 INOX | 116441    |

## PACKS

The J275 F 2K20 INOX comes with:

- AISI 316L satin-finished stainless steel cylinder
- flashing LED lights ring\*