



# Electronic pulse generators

## XTR B

### TECHNICAL SPECIFICATIONS



Model	XTR B	XTR B INOX
Installation type	wall or on column installation	
Power supply voltage	Bus 2easy, with 2 non polarised wires 24 V $\overline{\text{---}}$	
Max consumption	50 mA	
Max number of connectable READERS on the Bus2Easy control unit	14 (single channel) - 4 (two-channels)	
Protection class	IP54	
Dimensions (LxDxH)	100 x 21 x 72 mm	
TAG format	13,56 MHz Keyring	

Model	Description	Item code
XTR B	TAG Reader	786041
XTR B INOX	INOX TAG Reader	786040



Watch the "TAG XTR B reader" tutorial video

[vimeo.com/faacgroup/xtrb-en](https://vimeo.com/faacgroup/xtrb-en)

### INSTALLATION ACCESSORIES



Double high column H1000 (multiple quantity saleable 2 pcs)

401080



High column H1000 (multiple quantity saleable 2 pcs)

401075



Foundation plate for column

737100



External tube adapter

401064



Adapter for column or flush mounted <sup>♦</sup>

401065

### ACCESSORIES



Metal keytag (30 pcs pack)

401306



Keytag (30 pcs pack)

401048



XBR2 BUS-RELAY Interface 2CH

790064



XBR4 BUS-RELAY Interface 4CH

790065

### NOTE

♦ For wall installations with external or flush mounted pipe you must use the adaptors 401064 and 401065.